4-Wheel

Model Number S710LXW Weight Capacity 400 lbs. Maximum Speed¹ Up to 8 mph Ground Clearance³ 2.2" at motor, 3.15" at mid-frame Turning Radius³ 61.25" Overall Length³ 47" Overall Width³ 25.62" Seat-to-Ground Height 23" - 25" Seat-to-Deck Height 16.5" -18.5" Front Tires 3.5" x 10" solid Rear Tires 3.5" x 10" solid Suspension Front and rear Range Per Charge 1.2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries⁵ 160 lbs. Heaviest Piece When Disassembled³ 77 lbs. (front section) Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Battery Requirements⁴,6 Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger 5 amp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited Electronics: 2-year limited Battery: 6-months		
Maximum Speed¹ Up to 8 mph Ground Clearance³ 2.2" at motor, 3.15" at mid-frame Turning Radius³ 61.25" Overall Length³ 47" Overall Width³ 25.62" Seat-to-Ground Height 23" - 25" Seat-to-Deck Height 16.5" -18.5" Front Tires 3.5" x 10" solid Rear Tires 3.5" x 10" solid Suspension Front and rear Range Per Charge 1.2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries⁵ 160 lbs. Heaviest Piece When Disassembled³ 77 lbs. (front section) Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Battery Requirements⁴.6 Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger 5 amp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Model Number	S710LXW
Ground Clearance ³ 2.2" at motor, 3.15" at mid-frame Turning Radius ³ 61.25" Overall Length ³ 47" Overall Width ³ 25.62" Seat-to-Ground Height 23" - 25" Seat-to-Deck Height 16.5" -18.5" Front Tires 3.5" x 10" solid Rear Tires 3.5" x 10" solid Suspension Front and rear Range Per Charge 1,2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries ⁵ 160 lbs. Heaviest Piece When Disassembled ³ 77 lbs. (front section) Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Battery Requirements ^{4,6} Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger 5 amp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Weight Capacity	400 lbs.
Turning Radius ³ Overall Length ³ 47" Overall Width ³ 25.62" Seat-to-Ground Height 16.5" - 18.5" Front Tires 3.5" x 10" solid Rear Tires 3.5" x 10" solid Suspension Front and rear Range Per Charge 1,2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries ⁵ Heaviest Piece When Disassembled ³ 77 lbs. (front section) Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Pual Braking System Rear-wheel drive, sealed transaxle with 24-volt DC motor Regenerative and electromechanical Battery Requirements ^{4,6} Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Maximum Speed ¹	Up to 8 mph
Overall Length³ Overall Width³ 25.62" Seat-to-Ground Height 23" - 25" Seat-to-Deck Height 16.5" -18.5" Front Tires 3.5" x 10" solid Rear Tires 3.5" x 10" solid Suspension Front and rear Range Per Charge 1.2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries5 Heaviest Piece When Disassembled³ Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger 5 amp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Ground Clearance ³	2.2" at motor, 3.15" at mid-frame
Overall Width³ Seat-to-Ground Height Seat-to-Deck Height Front Tires 3.5" x 10" solid Rear Tires 3.5" x 10" solid Suspension Front and rear Range Per Charge 1,2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries5 Heaviest Piece When Disassembled³ Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Para-wheel drive, sealed transaxle with 24-volt DC motor Regenerative and electromechanical Battery Requirements4,6 Battery Charger Samp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Turning Radius ³	61.25"
Seat-to-Ground Height 23" - 25" Seat-to-Deck Height 16.5" - 18.5" Front Tires 3.5" x 10" solid Rear Tires 3.5" x 10" solid Suspension Front and rear Range Per Charge 1,2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries 5 Heaviest Piece When Disassembled 77 lbs. (front section) Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Battery Requirements 4,6 Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger 5 amp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Overall Length ³	47"
Seat-to-Deck Height Front Tires 3.5" x 10" solid Rear Tires 3.5" x 10" solid Suspension Front and rear Range Per Charge 1,2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries 5 Heaviest Piece When Disassembled 77 lbs. (front section) Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Battery Requirements 4,6 Battery Charger 5 amp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Overall Width ³	25.62"
Front Tires 3.5" x 10" solid Rear Tires 3.5" x 10" solid Suspension Front and rear Range Per Charge 1,2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries 5 Heaviest Piece When Disassembled 3 Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Pual Braking System Rear-wheel drive, sealed transaxle with 24-volt DC motor Regenerative and electromechanical Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Seat-to-Ground Height	23" - 25"
Rear Tires 3.5" x 10" solid Front and rear Range Per Charge 1.2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries 5 Heaviest Piece When Disassembled 3 Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Battery Requirements 4.6 Battery Charger Samp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Seat-to-Deck Height	16.5" -18.5"
Suspension Range Per Charge 1,2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries ⁵ Heaviest Piece When Disassembled ³ Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger 5 amp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Front Tires	3.5" x 10" solid
Range Per Charge 1,2 Up to 19.7 miles at 200 lbs. Up to 13 miles at 400 lbs. Total Weight Without Batteries ⁵ Heaviest Piece When Disassembled ³ Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Prive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Pual Braking System Regenerative and electromechanical Battery Requirements ^{4,6} Battery Charger Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Rear Tires	3.5" x 10" solid
Range Per Charge 1/2 Up to 13 miles at 400 lbs. Total Weight Without Batteries 5 Heaviest Piece When Disassembled 3 Standard Seating Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Battery Requirements 4,6 Battery Charger Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Suspension	Front and rear
Without Batteries ⁵ Heaviest Piece When Disassembled ³ 77 lbs. (front section) Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Battery Requirements ^{4,6} Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Range Per Charge ^{1,2}	
When Disassembled ³ Type: Limited reclining high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Drive System Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Battery Requirements ^{4,6} Battery Charger Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited		160 lbs.
Standard Seating high-back Weight: 43 lbs. Material: Black Vinyl Dimensions: 18" width, 18" depth Rear-wheel drive, sealed transaxle with 24-volt DC motor Dual Braking System Regenerative and electromechanical Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger Samp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited		77 lbs. (front section)
Drive System with 24-volt DC motor Regenerative and electromechanical Size: (2) 50 AH Weight: 30.2 lbs. each Battery Charger 5 amp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Standard Seating	high-back Weight: 43 lbs. Material: Black Vinyl
Battery Requirements ^{4,6} Battery Charger Size: (2) 50 AH Weight: 30.2 lbs. each Samp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Drive System	
Battery Requirements Weight: 30.2 lbs. each Battery Charger 5 amp, off-board Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Dual Braking System	
Warranty Frame: lifetime limited Drivetrain: 2-year limited Electronics: 2-year limited	Battery Requirements ^{4,6}	
Warranty Drivetrain: 2-year limited Electronics: 2-year limited	Battery Charger	5 amp, off-board
	Warranty	Drivetrain: 2-year limited Electronics: 2-year limited

HCPCS Code: K0899

POWER MOBILITY DEVICE, NOT CODED BY DME PDAC OR DOES NOT MEET CRITERIA

- 1 Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition, and tire condition. This specification can be subject to a variance of (+ or -) 10%.
- 2 Tested in accordance with ANSI/RESNA, MC Vol2, Section 4 & ISO 7176-4 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Test conducted at maximum weight capacity.
- 3 Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or -) 3%.
- 4 Battery weight may vary based on battery manufacturer.
- 5 Includes standard seat weight.
- 6 AGM or gel cell type required.



(US) 800-800-8586 • (Canada) 888-570-1113 pridemobility.com

HCPCS codes provided should not be considered as legal advice and do not guarantee reimbursement. DME providers are responsible for determining appropriate billing codes when submitting for insurance reimbursement.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tire pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of + or $-3\,$ %. Special order seats or non-standard dimensions will not be fold-flat and depth-adjustable.

VICLXSPORT_020119





Maintain your active lifestyle with the Victory® LX Sport. Equipped with Comfort-Trac Suspension (CTS), the Victory LX Sport easily handles more varied terrain while providing a smooth and comfortable ride. Enjoy convenient storage and a courtesy light under the tiller. A long-lasting LED headlight ensures optimal pathway illumination. Experience great features and a sporty style with the Victory LX Sport.

- CTS Suspension includes adjustable shocks for greater comfort
- Exclusive one-hand feather touch disassembly
- Charger port located on the tiller lets you conveniently charge your scooter
- Delta tiller with ergonomic wraparound handles lets you operate the scooter with one hand and rest your wrist
- · Easy-to-read LED voltmeter
- Rearview mirror

Available Colors





True Blue

Candy Apple Red

Optional Seating

Limited recline, black vinyl, high back with height adjustable headrest, flip-up height and width adjustable armrests

- · 22"x 18"
- 20" x 20"

Accessories

- Cane/crutch holder (single, double)
- Cell phone holder
- Cup holder
- Forearm crutch holder
- Oxygen tank holder
- Quad cane holder
- Rear basket
- Additional rearview mirror
- Saddlebag
- Safety flag
- Walker holder
- Weather cover
- Wishbone crutch holder
- XLR USB charger
- Lap belts: 50", 60" and 70"

Military Patches

