Home Care Technical Specification

Ultima Grab Bar w/ Curl Grip

LR8700D3G R8700D3G

Stock Numbers:

- □ R8712D3GBN 12" Ultima Grab Bar w/ Curl Grip Brushed Nickel Finish,, 1 ¼" Bar □ LR8716D3GBN – 16" Ultima Grab Bar w/Curl Grip
- Brushed Nickel Finish, 1 ¼" Bar

 R8718D3GBN 18" Ultima Grab Bar w/Curl Grip

 Brushed Nickel Finish, 1 ¼" Bar
- LR8724D3GBN 24" Ultima Grab Bar w/ Curl Grip
- Brushed Nickel Finish, 1 ¼" Bar

 R8736D3GBN 36" Ultima Grab Bar w/ Curl
- Grip
 Brushed Nickel Finish, 1 ¼" Bar
 Wholesale Packaging
- ☐ R8748D3GBN 48" Ultima Grab Bar w/Curl Grip Brushed Nickel Finish, 1 ¼" Bar
- R8742D3GBN 42" Ultima Grab Bar w/ Curl Grip
 - Brushed Nickel Finish, 1 1/4" Bar Wholesale Packaging
- □ R8712D3GCH 12" Ultima Grab Bar w/Curl Grip Chrome Finish
- ☐ LR8716D3GCH 16" Ultima Grab Bar w/ Curl Grip Chrome Finish. 1 ¼" Bar
- R8718D3GCH 18" Ultima Grab Bar w/Curl Grip Chrome Finish
- ☐ LR8724D3GCH 24" Ultima Grab Bar w/ Curl Grip Chrome Finish, 1 1/4" Bar
- R8736D3GCH 36" Ultima Grab Bar w/ Curl
 - Chrome Finish, 1 ¼" Bar Wholesale Packaging
- R8742D3GCH 42" Ultima Grab Bar w/ Curl
 - Chrome Finish, 1 1/4" Bar
- R8748D3GCH 48" Ultima Grab Bar w/Curl Grip Chrome Finish
- ☐ R8712D3GOWB 12" Ultima Grab Bar w/Curl Grip
 - Old World Bronze Finish
- LR8716D3GOWB 16" Ultima Grab Bar w/ Curl Grip
- Old World Bronze Finish, 1 ¼" Bar
- R8718D3GOWB 18" Ultima Grab Bar w/Curl Grip Old World Bronze Finish
- ☐ LR8724D3GOWB 24" Ultima Grab Bar w/ Curl Grin
- Old World Bronze Finish, 1 ¼" Bar

 R8736D3GOWB 36" Ultima Grab Bar w/Curl
- Grip
 Old World Bronze Finish
- R8742D3GOWB 42" Ultima Grab Bar w/Curl Grip
- Old World Bronze Finish


 R8748D3GOWB 48" Ultima Grab Bar w/Curl
 - Old World Bronze Finish

Materials:

1 1/4" **Grab Bar** rods are formed from (.040) type 304 stainless steel tubing.



Dimensions:



	12"	16"	18"	24"	36"	42"	48"
	Bars						
Α	12.00	16.00	18.00	24.00	36.00	42.00	48.00
В	15.15	19.15	21.15	27.15	39.15	45.15	51.15
С	3.15	3.15	3.15	3.15	3.15	3.15	3.15
D	2.75	2.75	2.75	2.75	2.75	2.75	2.75
Е	1.25	1.25	1.25	1.25	1.25	1.25	1.25

Installation Instructions:

- 1. Please note that screws MUST be mounted into a wood stud for secure installation.
- Slide the decorative cover away from the hub end to expose the SecureMount™
 mounting flange. Do not remove protective plastic from decorative cover until
 indicated later in these instructions.
- 3. Locate the studs behind the wall by using a stud sensor or other stud locating method. Studs are usually 16 in. apart; locate the center of each stud.
- 4. Moving aside the decorative cover as needed, with a pencil, mark three of the mounting locations on each of the two grab bar flanges. Two marks to be made above the grab bar in the area indicated in the illustration below. The third mark to be made below the grab bar in the area indicated in the illustration below. Decide whether you would like to position your grab bar horizontally, vertically or at an angle, remembering that BOTH ends of the grab bar MUST be positioned over a wood stud.
- 5. Moving the decorative cover as far away from the marked slots as possible, drill a hole into the marks, through the slots (as shown in illustration). Position the drill at a slight angle in order to get around the grab bar and decorative cover, making sure to drill into the wood stud. If desired, apply silicone caulk to the back of the decorative cover to guard against water penetration.
- To mount the grab bar, reposition one end of the grab bar SecureMount™ mounting flange over the marked holes.
- 7. Thread a washer onto each screw. Using the screwdriver, screw the wood screws with washers into the SecureMount™ mounting flange at one end of the grab bar. Then screw the wood screws with washers into the mounting flange at the other end of the grab bar.
- 8. Tighten the screws until secure.
- Slide the decorative cover over the SecureMount™ mounting flange, rotating to find the correct fit before snapping into place.
- 10. Slide decorative covers over SecureMount™ mounting flanges.

Stock Number:	Grab Bars
By Creative Specialties	

25300 AL MOEN DRIVE • NORTH OLMSTED, OH 44070 CORPORATE HEADQUARTERS: (800) 321-8809 • FAX: (800) 848-6636 INTERNATIONAL: (440) 962-2000 • FAX: (440) 962-2726 CUSTOMER SERVICE (USA): 800-882-0116 • FAX: (888) 379-2720 WWW.MOEN.COM